

<p><b>1</b> Painting</p>	<p><b>2</b> Cleaning</p> <p>siachrome magic, microfibre cloth</p>	<p><b>3</b> Sanding out of dust inclusions</p> <p>1913 siawat</p>	<p><b>4</b> Refining areas</p> <p>7940 siaair</p>	<p><b>5</b> Removal of polishing scratches</p> <p>siachrome cut, yellow polishing disc</p>
<p><b>6</b> Cleaning</p> <p>siachrome magic, microfibre cloth</p>	<p><b>7</b> Removal of holograms</p> <p>siachrome finish, black polishing disc</p>	<p><b>8</b> Cleaning</p> <p>siachrome magic, premium cloth</p>	<p><b>Best practice: Paint sealing</b></p> <p>siachrome pearl and platinum are suitable for the durable glazing of all automotive varnishes and provide a unique deep-gloss finish. They protect the varnish reliably against washing scratches, tar, bird droppings, acid rain and UV rays.</p>	

In the application steps listed a recommendation is concerned; the steps must be adapted according to the requirements. No legal decision can be deduced from this recommendation.

## Abrasives and polishing system

1913 siawat Ø 37 mm Art. ID: 4269.7970.xxxx	7940 siaair Ø 90 mm: 3647.2462.xxxx Ø 150 mm: 5163.3687.xxxx	siachrome cut Scratch remover, 1 kg Art. ID: 0020.6663.01	siachrome finish Finishing paste, 1 kg Art. ID: 0020.6664.01	siachrome pearl Paint sealing, 1 l Art. ID: 0020.6667.01	siachrome platinum Premium paint wax Art. ID: 0020.6665.01	siachrome magic Power cleaner, 0.5 l Art. ID: 0020.6666.01
Lambs-wool pad, siafast Ø 135 mm: 0020.6674.01 Ø 85 mm: 0020.6673.01	Yellow polishing pad, siafast Ø 145 mm: 0020.6671.02 Ø 85 mm: 0020.6672.02	Black polishing pad, siafast Ø 145 mm: 0020.6676.02 Ø 85 mm: 0020.6675.02	Application puck Ø 130 mm Art. ID: 0020.6668.01	Microfibre cloth 380 x 380 mm Art. ID: 0020.3185.01	Premium cloth 400 x 400 mm Art. ID: 0020.6670.01	

## Polishing guide

- For best results, use the recommended pad and polish combinations.
- Hold the pad at a slight angle to the surface to be polished (this reduces the hologram effect).
- To avoid spraying polish into the surrounding area, start at a low speed. Then increase the speed gradually to max. 2000 rpm.
- Reduce the pressure while polishing.
- Keep the pads clean – dirty pads cause scratches. Clean the pads with water after use. This will also extend the lifetime of the polishing pads.