



Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

siachrome PEARL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products

1.3. Details of the supplier of the safety data sheet

Company name:	Sia Abrasives Industries AG	
Street:	Mühlwiesenstrasse 20	
Place:	CH-8501 Frauenfeld/Schweiz	
Telephone:	+41 (0)52 724 41 11	Telefax: +41 (0)52 724 45 45
e-mail:	msds.ch@sia-abrasives.com	
Internet:	www.sia-abrasives.com	

1.4. Emergency telephone

Toxzentrum Zürich 0041 44 251 51 51

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EG) Nr. 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EG) Nr. 1272/2008

Hazard components for labelling

This product has been treated with biocides for preservation.

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P273	Avoid release to the environment.
P501	Dispose of waste according to applicable legislation.

Special labelling of certain mixtures

EUH208 Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 2 of 14

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EG) Nr. 1272/2008)			
8042-47-5	white mineral oil (petroleum)			1 - < 5 %
	232-455-8		01-2119487078-27	
	Asp. Tox. 1; H304			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene			1 - < 5 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			1 - < 5 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411 EUH066			
64-17-5	ethanol			1 - < 5 %
	200-578-6		01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
67-63-0	isopropanol			1 - < 5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)			< 0.1 %
	611-341-5	613-167-00-5		
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
8042-47-5	232-455-8	white mineral oil (petroleum)	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene	1 - < 5 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
64742-49-0	927-510-4	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	1 - < 5 %
		dermal: LD50 = >2920 mg/kg; oral: LD50 = >5840 mg/kg	
64-17-5	200-578-6	ethanol	1 - < 5 %
		inhalation: LC50 = 117-125 mg/l (vapours); dermal: LD50 = 17100 mg/kg; oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
67-63-0	200-661-7	isopropanol	1 - < 5 %
		dermal: LD50 = 12800 mg/kg; oral: LD50 = 5840 mg/kg	
55965-84-9	611-341-5	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)	< 0.1 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = >141 mg/kg; oral: LD50 = 66 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 Aquatic Acute 1; H400: M=100 Aquatic Chronic 1; H410: M=100	

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 3 of 14

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No special measures are necessary.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Remove all sources of ignition. Ventilate affected area. Wear personal protection equipment (refer to section 8).

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Use personal protection equipment. Tested protective gloves must be worn: Recommended material: NBR (Nitrile rubber). Unsuitable material: PVC (polyvinyl chloride)

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 4 of 14

6.3. Methods and material for containment and cleaning up

For containment

Collect spillage. Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Use non-sparking tools. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

Further information on storage conditions

Recommended storage temperature: 15-25°C

7.3. Specific end use(s)

Automotive care products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
1332-58-7	Kaolin respirable dust	-	2		TWA (8 h)	WEL
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 5 of 14

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
8042-47-5	white mineral oil (petroleum)		
Consumer DNEL, long-term	inhalation	systemic	35 mg/m ³
Consumer DNEL, long-term	dermal	systemic	93 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	160 mg/m ³
Worker DNEL, long-term	dermal	systemic	220 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	40 mg/kg bw/day
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes		
Consumer DNEL, long-term	dermal	systemic	149 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	2085 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	477 mg/m ³
Consumer DNEL, long-term	oral	systemic	149 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	300 mg/kg bw/day
64-17-5	ethanol		
Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
Worker DNEL, acute	inhalation	local	1900 mg/m ³
Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
Consumer DNEL, acute	inhalation	local	950 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	114 mg/m ³
67-63-0	isopropanol		
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³
Worker DNEL, long-term	inhalation	systemic	500 mg/m ³

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 6 of 14

PNEC values

CAS No	Substance	Value
Environmental compartment		
64-17-5	ethanol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,38 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
67-63-0	isopropanol	
Freshwater		140,9 mg/kg
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Soil		28 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Use only in well-ventilated areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Recommended glove articles: HyFlex® Foam (EN 420, EN 388 (3131)).

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: white

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 7 of 14

Odour:	characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		>78 °C
Flammability		
Solid/liquid:		not applicable
Gas:		not applicable
Lower explosion limits:		0,5 vol. %
Upper explosion limits:		7 vol. %
Flash point:		> 61 °C
Auto-ignition temperature:		>200 °C
Decomposition temperature:		not determined
pH-Value (at 20 °C):		7,1
Viscosity / kinematic: (at 40 °C)		>20,5 mm ² /s
Water solubility:		completely miscible
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure: (at 20 °C)		<0,1 hPa
Vapour pressure: (at 50 °C)		not determined
Density (at 20 °C):		0,96 g/cm ³
Relative density:		not determined
Bulk density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties
Not oxidising.

Other safety characteristics

Solvent content: 11,25 %
Viscosity / dynamic:
(at 20 °C) 5000-10000 mPa·s

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Strong acid. Strong alkali. Highly oxidising substances.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 8 of 14

11.1. Information on hazard classes as defined in CLP Regulation

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
8042-47-5	white mineral oil (petroleum)				
	oral	LD50 >5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA	OECD 402
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene				
	oral	LD50 >5000 mg/kg	Rat	ECHA	OECD TG 401
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA	OECD TG 402
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes				
	oral	LD50 >5840 mg/kg	Rat		OECD 401
	dermal	LD50 >2920 mg/kg	Rabbit		OECD 402
64-17-5	ethanol				
	oral	LD50 10470 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 17100 mg/kg	Rabbit	ECHA	
	inhalation (4 h) vapour	LC50 117-125 mg/l	Rat	ECHA	OECD 403
67-63-0	isopropanol				
	oral	LD50 5840 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 12800 mg/kg	Rabbit	GESTIS	
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)				
	oral	LD50 66 mg/kg	Rat	Thor	
	dermal	LD50 >141 mg/kg		Thor	
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 9 of 14

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
8042-47-5	white mineral oil (petroleum)					
	Acute fish toxicity	LL50 >1000 mg/l	96 h	Leuciscus idus (golden orfe)	ECHA	OECD 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EL50 >100 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
	Algae toxicity	NOEC >=100 mg/l	72 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	OECD 203
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes					
	Acute fish toxicity	LL50 13,4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	
	Acute algae toxicity	ErC50 10-30 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EL50 3 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	
64-17-5	ethanol					
	Acute fish toxicity	LC50 11200 mg/l	96 h	Salmo gairdneri	ECHA	US EPA method E03-05
	Acute algae toxicity	ErC50 275 mg/l	72 h	Chlorella vulgaris	ECHA	OECD 201
	Acute crustacea toxicity	EC50 5012 mg/l	48 h	Ceriodaphnia dubia	ECHA	ASTM E729-80
	Algae toxicity	NOEC 280 mg/l	7 d	Lemna gibba (swollen duckweed)	ECHA	
67-63-0	isopropanol					
	Acute fish toxicity	LC50 9640 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 9714 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)					
	Acute fish toxicity	LC50 0,22 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 203
	Acute algae toxicity	ErC50 0,048 mg/l	72 h	Pseudokirchneriella subcapitata	Thor	OECD 201
	Acute crustacea toxicity	EC50 0,1 mg/l	48 h	Daphnia magna (Big water flea)	Thor	OECD 202
	Fish toxicity	NOEC 0,098 mg/l	28 d	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 210
	Algae toxicity	NOEC 0,0012 mg/l	3 d	Pseudokirchneriella subcapitata	Thor	OECD 201

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 11 of 14

	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna (Big water flea)	Thor	OECD 211
	Acute bacteria toxicity	(EC50 mg/l)	7,92	3 h	Activated sludge		OECD 209

12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
8042-47-5	white mineral oil (petroleum)			
	OECD 301F	31 %	28	ECHA
	Not readily biodegradable (according to OECD criteria)			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene			
	OECD 301 F	80%	28	ECHA
	Readily biodegradable (according to OECD criteria).			
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			
	OECD 301 F	98%	28	ECHA
	Readily biodegradable (according to OECD criteria).			
64-17-5	ethanol			
		84%	20	ECHA
	Readily biodegradable (according to OECD criteria).			
67-63-0	isopropanol			
	EU Method C.5	53%	5	ECHA
	Readily biodegradable (according to OECD criteria).			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)			
	OECD 301 A	>70 %	28	Thor
	Readily biodegradable (according to OECD criteria).			
	OECD 301 D	>60%		Thor
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
8042-47-5	white mineral oil (petroleum)	>4
64-17-5	ethanol	-0,31
67-63-0	isopropanol	0,05

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	3,2		ECHA
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)	3,16		EPIWIN, S 1177

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 12 of 14

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No special measures are necessary.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 13 of 14

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2010/75/EU (VOC): 7,402 % (71,064 g/l)

2004/42/EC (VOC): 7,404 % (71,076 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

(EU) EINECS/ELINCS/NLP: yes

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 6,7,9,12,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome PEARL

Revision date: 30.11.2022

Page 14 of 14

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
2	Automotive care products, Industrial uses	IS	-	-	7, 10, 17	4	-	-	
3	Automotive care products, Professional uses	PW	-	-	10, 11, 17	8a	-	-	
4	Automotive care products, Consumer use	C	-	31	-	8a	-	-	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)