## **Technical data sheet** 1815 siatop



Status:	Ok
Approval:	24.01.2022

Classification	Public series
Product type:	Coated abrasives
Main industries:	General Fabrication Aerospace
Further industries:	Trucks Rail Marine Bus Wind Power Machinery, equipment Coils and Sheet Metal Machinery, equipment Tubes and Profiles

Product profile		
Grit type:	Zirconia alumina	
Grit range (total):	24; 36-320; 400	P100 – P400 FEPA P / ISO 6344 24 – 80 ANSI
Backing:	Fibre f-wt paper (FSC-certified)	24 - 40 40 - P400
Coating:	Closed	
Bonding:	Resin over resin	
Special coating:	Cooling additive	
Equipment:		

Properties		Technology
Removal rate:	8 - high	- Plain
Lifetime:	8 - long	- siafast
Finishing:	9 - very good	
Flexibility:	3 - rigid	
Contact pressure:	7 - strong	

Advantages	Advantages		
General Fabrication:	<ul> <li>Versatile all-round product with an attractive range of options</li> <li>Outstanding performance in dry sanding applications</li> <li>Fast and rugged stock removal with regular surface quality</li> <li>Cost reduction thanks to long lifetime</li> <li>Minimal effort required for high stock removal</li> <li>Excellent surface quality</li> </ul>		
Aerospace:	<ul> <li>Outstanding performance in dry sanding applications</li> <li>Fast and safe change of abrasive with siafast hook and loop fastening system</li> <li>The low-cost alternative to fibre discs</li> <li>Minimal effort required for high stock removal</li> </ul>		



Applications	Applications		
General Fabrication:	<ul> <li>Removal of paint</li> <li>Removal of rust</li> <li>Weld preparation</li> <li>Removal of discolouration</li> <li>Stock removal</li> <li>Deburring</li> <li>Surface treatment</li> <li>Smoothing and blending of flaws</li> <li>Structuring and final sanding</li> </ul>		
Aerospace:	<ul> <li>Removal of paint</li> <li>Removal of rust</li> <li>Weld preparation</li> <li>Removing discolouration</li> <li>Stock removal</li> <li>Surface treatment</li> <li>Deburring</li> </ul>		

Material		
General Fabrication:	Non-ferrous metals	<ul> <li>Non-ferrous metal</li> </ul>
	Stainless steel	<ul> <li>High-alloy steels</li> </ul>
	Steel	<ul> <li>Unalloyed / low-alloy steel</li> </ul>
Aerospace:	Composites	Composite

<b>Conversion forms</b>	Upper conversion	Lower conversion
	Rolls	- Jumbo rolls - siafast rolls
	Strips	- siafast strips
•	Discs	- siafast discs - Various discs
	Belts	<ul> <li>Wide belts (width: from 400 mm)</li> <li>Narrow, edge and long belts (width: 25– 399 mm/length: up to 10,700 mm)</li> </ul>

Application	Superordinate group	Subgroup
- Star -	Portable machine sanding	Angle grinder
E	Portable machine sanding	random orbital sander
	Stationary belt sanding	Contact wide belt sanding
	Stationary belt sanding	Long belt sanding
	Stationary machine sanding	Stationary disc sanding

## Technical data sheet 1815 siatop



Application	Superordinate group	Subgroup
Cut:	Dry application	

Details	
No suitability for:	<ul> <li>In heavy duty use</li> <li>glass sanding</li> <li>Wet sanding</li> <li>Stone grinding</li> </ul>
Sanding recommendation:	<ul> <li>Designed for universal use thanks to co-ordinated product parameters</li> <li>Good adhesion of hook and loop backing to the new siatop siafast grinding pad</li> </ul>
Safety recommendation:	Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety
	<ul> <li>Pay attention to the abrasives safety data sheet (available from sia Abrasives)</li> <li>Follow the general FEPA safety recommendations</li> <li>Use eye and face protection</li> <li>Use an effective dust extraction unit or wear a fine dust mask</li> </ul>

Communication				
Claim:	For fast and cost-effective surface	For fast and cost-effective surface treatment of steel and non-ferrous metals		
Сору:	1815 siatop impresses with its hig	1815 siatop impresses with its high removal rate, long lifetime and very good finish.		
Image material:	Product Top View (PTV)	Front side: Rear side:	ID ID	
	Application image	General Fabrication: Aerospace:	ID 5617 ID 6385	
	Product show:			
	Macro shot:			
	Packaging image:			
	Product group image:		ID 12285	

Main applicationSecondary application