


| | |
|-----------|--------------|
| Status: | not approved |
| Approval: | |

| | |
|-----------------------|---------------------|
| Classification | Public series |
| Product type: | |
| Main industries: | General Fabrication |
| Further industries: | |

| | |
|------------------------|------------------|
| Product profile | |
| Grit type: | Aluminium oxide |
| Grit range (total): | |
| Backing: | Nonwoven / cloth |
| Coating: | |
| Bonding: | Resin over resin |
| Special coating: | |
| Equipment: | |

| | | |
|-------------------|--|-------------------|
| Properties | | Technology |
| Removal rate: | | |
| Lifetime: | | |
| Finishing: | | |
| Flexibility: | | |
| Contact pressure: | | |

| | | |
|---|--------------------------|------------------|
| Application | Superordinate group | Subgroup |
|  | Portable machine sanding | Straight grinder |
| Cut: | | |

| | |
|-------------------------|--|
| Details | |
| No suitability for: | |
| Sanding recommendation: | |
| Safety recommendation: | <p>Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety</p> <ul style="list-style-type: none"> - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Follow the general FEPA safety recommendations - Use eye and face protection |



| Communication | |
|----------------------|---|
| Claim: | For faster surface finishing in portable machine sanding |
| Copy: | The spindle mounted flap wheels with alternated nonwoven and coated abrasive flaps offer light blending capability along with an even surface finish thanks to alternate nonwoven and coated flaps. |
| Image material: | Product Top View (PTV) Front side: ID Rear side: ID |
| | Application image |
| | Product show: |
| | Macro shot: |
| | Packaging image: |
| | Product group image: |

- Main application
- Secondary application