



# 1950 siaspeed

For a perfect finish at full speed



## For a perfect finish at full speed

The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.

- ▶ Very high stock removal rates and excellent finish
- ▶ Performance-enhancing grit mix with ceramic aluminium oxide in 40 - 80 grit range
- ▶ Minimal clogging thanks to open coating in 220 - 600 grit range
- ▶ Long lifetime
- ▶ Lower abrasive consumption
- ▶ Versatile all-round product with an attractive range of options

### Product profile

Grit type:	Mixed grit with ceramic content	40 – 80
	Semi-friable aluminium oxide / blue-fired	P100 – P400
	White aluminium oxide	P500 – 1500
Grit range:	40; 60-1500	
Backing:	Paper (FSC-certified)	40 – 600
	Film	800 – 1500
Coating:	Electrostatic	40 – 180
	Electrostatic open	220 – 600
	Special process	800 – 1500
Bonding:	Resin over resin	
Special coating:	Stearate	from 80

### Use



### Applications

- Sanding of coatings and impurities
- Sanding out unevenness at the edges of repaired surfaces
- Flatting of bodyfiller and composite materials
- Fine sanding of primer filler
- Keying of old and new lacquers
- Producing a matt finish on old and new lacquers for blending
- Removal of orange peel effect and dust inclusions
- Preparation for polishing on high-gloss surfaces

### Materials

Colour; Primer filler; Bodyfiller; Lacquer; Old lacquer; Primer coat; Epoxy primer coat; Cathodic dip primer coat; Plastics; Acrylic glass; Gelcoat polyester; Glass-fibre reinforced plastic (GRP)

### Technology

Open coating; Plain; S Performance; siafast; siasoft