



# 1950 siaspeed

For a perfect finish at full speed



## For a perfect finish at full speed

The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.

- ▶ High-performance abrasives
- ▶ High performance for stock removal
- ▶ Long lifetime
- ▶ A versatile all-round product
- ▶ Lower abrasive consumption
- ▶ Homogeneous sanding finish

### Product profile

Grit type:	Mixed grit with ceramic content	40 – 80
	Semi-friable aluminium oxide / blue-fired	P100 – P400
	White aluminium oxide	P500 – 1500
Grit range:	40; 60-1500	
Backing:	Paper (FSC™-certified)	40 – 600
	Film	800 – 1500
Coating:	Electrostatic	40 – 180
	Electrostatic open	220 – 600
	Special process	800 – 1500
Bonding:	Resin over resin	
Special coating:	Stearate	from 80

### Use



### Applications

- Keying of polyesters and composites
- Sanding out feather edges, flash rust and stone chips
- Shaping of bodyfillers and primer fillers
- Keying of new components and factory primers
- Sanding of old lacquer
- Producing a matt finish on old and new lacquers for blending
- Flattening of bodyfiller and primer filler
- Removal of orange peel effect and dust inclusions
- Preparation for polishing on high-gloss surfaces

### Materials

Colour; Primer filler; Bodyfiller; Lacquer; Old lacquer; Primer coat; Epoxy primer coat; Cathodic dip primer coat; Plastics; Acrylic glass; Gelcoat polyester; Glass-fibre reinforced plastic (GRP)

### Technology

Open coating; Plain; S Performance; siafast; siasoft