

## Technical data sheet

7988 siastrong



Status:	Ok
Approval:	28.05.2024

Classification	Public series
Product type:	Foam abrasives
Main industries:	Building Interior
Further industries:	Kitchens Windows and Doors Marine


Product profile	
Grit type:	Aluminium oxide
Grit range (total):	180; 240; 320
Backing:	Mesh
Coating:	Mechanical
Bonding:	Elastic binder
Special coating:	
Equipment:	




Properties	Technology
Removal rate:	- siastrong
Lifetime:	
Finishing:	
Flexibility:	
Contact pressure:	

Advantages	
Building Interior:	<ul style="list-style-type: none"><li>- Maximum useful life</li><li>- Highly adaptable to contours, curves and profiles</li><li>- Low clogging</li><li>- Can be used many times</li><li>- Consistent performance throughout the life of the product</li><li>- Can be used wet or dry</li></ul>

Applications	
Building Interior:	<ul style="list-style-type: none"><li>- Sanding off old varnish, paints and stains</li><li>- Sanding off raised wooden fibres</li><li>- Keying surfaces for better paint adhesion</li></ul>

<b>Material</b>		
Building Interior:		<ul style="list-style-type: none"> <li>○ Acrylic glass</li> <li>○ Plastics</li> <li>○ Melamine sheet</li> <li>○ Bodyfiller</li> <li>● Water-based lacquer</li> <li>● UV lacquer</li> <li>● Polyester lacquer</li> <li>○ NC lacquer</li> <li>● PU lacquer</li> <li>● Stainless steel (inox)</li> <li>○ Solid surface material</li> <li>● Old lacquer</li> <li>● Old paint</li> <li>● Colour</li> <li>○ Plaster</li> <li>● Primer filler</li> <li>● Hard wood</li> <li>● Soft wood</li> </ul>
	Bodyfiller	
	Lacquers	
	Lacquers	
	Lacquers	
	Lacquers	
	Lacquers	
	Metals	
	Mineral materials	
	Old lacquer	
	Old paint	
	Paints	
	Plaster	
	Primer filler	
	Wood	
	Wood	

<b>Conversion forms</b>	Upper conversion	Lower conversion
	Sheet	- Half sheets

<b>Application</b>	Superordinate group	Subgroup
	Manual sanding	Manual sanding
	Manual sanding	Hand sanding for profiles
	Manual sanding	Hand sanding for edges
Cut:	Dry application, Wet sanding	

<b>Details</b>	
No suitability for:	
Sanding recommendation:	
Safety recommendation:	Observe the current valid safety recommendations at: <a href="http://www.sia-abrasives.com">www.sia-abrasives.com</a> > Expertise > Safety



Communication			
Claim:	Robust and highly versatile		
Copy:	The double-sided 7988 siastrong can be used in a wide variety of applications. Its perforation ensures sharp contours and makes precise sanding easy, even in hard-to-reach places. The robust abrasive is washable, hard-wearing and durable.		
Image material:	Product Top View (PTV)	Front side:	ID
		Rear side:	ID
	Application image	Building Interior:	ID 115582
	Product show:		
	Macro shot:		
	Packaging image:		
	Product group image:		ID 115654

- Main application
- Secondary application