



7983 siasponge flex

Adapts perfectly to the workpiece

Medium	120–180	
Fine	240–320	
Superfine	500–600	
Ultrafine	800–1000	
Microfine	1200–1500	

Adapts perfectly to the workpiece

Be it curves, shapes or contours – an even and perfect sanding pattern can be achieved with 7983 siasponge flex. The extra-soft foam of siasponge flex ensures maximum conformability.

- ▶ Colour coded for easy identification
- ▶ Foam backing equalises pressure and prevents undercutting
- ▶ Highly adaptable to contours, curves and profiles
- ▶ Low clogging
- ▶ Can be used many times
- ▶ Consistent performance throughout the life of the product
- ▶ Can be used wet or dry

Product profile

Grit type:	Aluminium oxide
Grit range:	60-220; 280
Backing:	PU foam (soft)
Coating:	Mechanical
Bonding:	Elastic binder
Coating:	2-sided

Applications

- Sanding off old varnish, paints and stains
- Sanding off raised wooden fibres
- Keying surfaces for better paint adhesion

Materials

Old paint; Old lacquer; Colour; Primer filler; Melamine sheet; NC lacquer; PU lacquer; Bodyfiller; Polyester lacquer; UV lacquer; Water-based lacquer; Plastics; Solid surface material; Hard wood; Soft wood; Plaster

Use

